

# CLEAN AIR HEAT

**K275-FAI**  
**HEAT OUTPUT**  
**275,000 BTU/HR**



## PORTABLE DIESEL INDIRECT FIRED HEATERS

**K150-FAI**  
**HEAT OUTPUT**  
**150,000 BTU/HR**



- Powerful fans ensure high static pressure allowing heater placement outdoors with heated air directed indoors.
- Portable heaters include fuel tanks.
- Long life stainless steel combustion chamber.
- Heat exchanger to keep exhaust gas and hot air separate.
- Photoelectric flame sensor.
- Water resistant flame control box.
- Automatic electric safety and control devices.
- Can be connected to a accessory thermostat.
- Durable powder coated finish.
- Ideal for drying building sites and heating enclosed buildings.

**K-FAI series indirect fired heaters offer clean heated air for:**

- Construction Sites
- Warehouses
- Crop Drying
- Job Sites
- Tents
- Greenhouses
- Shops
- Animal confinement



FEATURES	Model K150-FAI	Model K275-FAI
Rated Heat Output (BTU/HR)	150,000	275,000
Output (CFM)	1,200	1,765
Static Pressure (in WC)	.71	.75
Temperature Increase (°F)	101°	104°
Fuel Consumption (Gal/Hr)	1.05	1.97
Power Required	115/60Hz	115/60Hz
Tank Capacity (gallon)	13.5	21.1
Combustion Air Exhaust Duct	5.5"	5.5
Heated Air Exhaust Duct	11.9"	15.7"
Length of Ductability (Ft.)	20'	40'
Dimensions (HxWxL)	41"x23"x42"	47"x26"x49"
Shipping Weight (lbs)	165	232